



PRODUCT HIGHLIGHTS

- Three phase, professional MIG/MAG welding, separate wire feeder, on wheel, fan cooled
- DC output, step voltage adjustment, stepless wire speed control, Intermittent welding time is adjustable, two-roller drive, four roller drive are optional
- Perfect with over heating, over load protection
- Excellent for solid wire and flux core wire
- Ideal equipment to weld mild carbon steel, mild alloy steel and stainless steel in industry use

INDUSTRIAL &
HEAVY INDUSTRIAL
Applications

Processes:
MIG/MAG, FCAW

TECHNICAL DATA

Model	DeltaMig-350
Input power (V)	400
Rated input current (A)	23
Rated input capacity (KVA)	15.1
Output open circuit voltage (V)	20-42
Welding current adjustment range (A)	60-360
Rated output (A)	60%@350
Weight (Kg)	155
Electrode diameter (mm)	0.8-1.2
Packing dimensions: L*W*H (mm/in.)	1000X590X840/39X23X32.8
Cod.	9.24.003

MANUFACTURED UNDER
ISO 9001
CERTIFIED
QUALITY
ASSURANCE SYSTEM



Lion International U.K (M.E.) Limited
Monomark House, 27 Old Gloucester Street, London WC1N 3XX, United Kingdom.
T: +44 20 74198760 F: +44 20 78319489 E: info@lionintweld.co.uk

Lion International Middle East FZC
P.O. Box 41654, W/H No. 1K-01/4, Hamriyah Free Zone, Sharjah, UAE.
T: +971 6 5260461 F: +971 6 5260561 E: info.me@lionintweld.co.uk